



FCS-4203 GEMINI Zoom Dome IP Camera, 2-MP, H.265

Product Images



Short Description

- 360° pan and 220° tilt movements allow for a wide range of monitoring angles
- Triple power support: 12V DC/24V AC/PoE (IEEE 802.3af 60W)
- Built-in Micro SD/SDHC card slot for local storage
- Video compression: H.264, H.265, MJPEG
- Power support: PoE (IEEE 802.3af)
- Vandal-proof IK10-rated housing
- Supports 4.3X optical zoom
- Built-in Micro SD/SDHC card slot for local storage

Beschreibung

The LevelOne FCS-4203 Fixed Dome Outdoor Camera offers a highly reliable, cost-effective outdoor IP surveillance solution in a low-profile dome mounted casing, which is rated at IP66 and able to withstand outdoor operating conditions such as rain, snow, extreme heat, dust and humidity. The FCS-4203 offers 2-Megapixel resolution, and with 802.3af standard PoE, can use a single Cat.5 cable to run both power and data, making deployments easy and flexible. The dome mounting prevents malicious tampering with the camera, making it a secure and smart choice for all outdoor installations.

Additional Information

Number of client	16
Data rate	2Kbps~16Mbps
Frame rate	First Stream:50Hz: 25fps (1920 × 1080, 1280 × 960, 1280×720)60Hz: 30fps (1920 × 1080, 1280 × 960, 1280×720)Sub Stream:50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)Third Stream:50Hz: 25fps (1920 × 1080, 128
Sicherheit	One-key reset, Anti-Flicker, heartbeat, mirror, password protection, privacy mask, Watermark, IP address filtering, Anonymous access
Video	Adjustable image size, quality and bit rate,3D Digital Noise Reduction,120 dB Wide Dynamic Range,Triple Video Streams Configurable brightness, sharpness, contrast, saturation, white balance and exposure-Motion detection
Power Consumption	12 VDC, 0.75A, max. 9.5W PoE0.3A to 0.1A, max. 11W
Approval and compliance	CE/FCC/UL,IK10,IP67
Max. operating temperature (°C)	60
Max. storage temperature (°C)	95
Min. operating temperature (°C)	-30
Supported browsers	Internet Explorer 9.0 or above
Angle of view (°)	Horizontal field of view: 105 to 35
Audio format	G.711/G.722.1/G.726/MP2L2, 64 Kbps (G.711)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 128 Kbps (MP2L2
Button	Reset Button
Digital zoom	8X
Image sensor	1/2.8" Progressive Scan CMOS
Indicators	Power
IR cut filter	Ja
IR range	Up to 30 meter
Lens	2.8 mm to 12 mm @ 1.4, motorized lens

Minimum illumination (lux)	Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR B/W: 0.0068 Lux @ (F1.4, AGC ON), 0 Lux with IR
Resolution	50Hz: 25fps (1920 * 1080, 1280 * 960, 1280*720) 60Hz: 30fps (1920 * 1080, 1280 * 960, 1280*720)
Shutter time	1/3 s to 1/100,000 s
Storage capacity	Support Micro SD/SDHC/SDXC card with ANR (up to 128G)
Standards	TCP/IP (IPv4), UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Video format	H.265/H.264/MJPEG
Weatherproof rating	IP67
General features	Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser
Product weight (kg)	1,287
Product breadth (mm)	133,1
Product depth (mm)	153,4
Product height (mm)	153,4
Color	White
EAN	4015867203415
Model number	FCS-4203
Package contents	FCS-4203 Screw Kit Resource CD (User Manual, Utility, 64-CH Monitoring Software)
Fast Ethernet RJ45	10/100 Mbps PoE 802.3af
MicroSD/TF card slot	Support Up to 128GB
3.5mm audio in/out	In x1, Out x1
Resolutions	1920*1080@30fps
Camera Type	Dome
Resistance	Weatherproof
Zoom Type	Motorization
2-way Audio	Ja

