



FCS-5092 GEMINI Fixed IP Camera, 5-MP, H.265, 802.3AF, POE, IR LEDS 50 Meter, INDOOR/OUTDOOR

Product Images





Short Description

- Free surveillance and CMS (Central Management System) software packages with 64-channel license
- Built-in Micro SD/SDHC card slot for local storage
- Built-in Micro SDHC/SDXC card slot for local storage
- Built-in infrared LEDs for night viewing up to 50m
- 5-Megapixel high-definition resolution
- Video compression: H.264, H.265
- Weatherproof IP67-rated housing

Description

The LevelOne FCS-5092 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 5-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5092 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Additional Information

Number of client	16
Data rate	32 Kbps to 16 Mbps
Frame rate	2560 × 1656 @ 20fps
Management	Behavior Analysis: Line crossing detection, intrusion detection, unattended baggage detection, object removal detection Line Crossing Detection: Cross a pre-defined virtual line, up to 1 pre-defined virtual lines supported Intrusion Detection: Enter an
Security	One-key Reset, Anti-Flicker, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter
Video	Support 1 fixed region for mainstream and sub stream separately
Power Consumption	7-9 W
Approval and compliance	CE/FCC, IP67
Compatibility	Microsoft Internet Explorer 11
Max. operating temperature (°C)	60
Max. storage temperature (°C)	95
Min. operating temperature (°C)	-30
Supported browsers	Microsoft Windows 8/7/Vista/XP/10
Angle of view (°)	63.5
Button	Reset Button
Image sensor	1/2.9" Progressive Scan CMOS
Indicators	Power
IR cut filter	Yes
IR range	Up to 50 meter
Lens	Fixed-focal, f=4mm, F2.0
Minimum illumination (lux)	Color: 0.01 lux @(F1.2, AGC ON), 0 lux with IR
Power supply	VDC12V, 1A/PoE 802.3af

Resolution	50Hz: 20 fps (2560 * 1656), 25 fps 2560 * 1440, 2048 * 1536, 1920 * 1080, 1280 *720) 60Hz: 20 fps (2560 * 1656), 30 fps 2560 * 1440, 2048 * 1536, 1920 * 1080, 1280 *720)
Shutter time	1/3 ~ 1/10,000 sec
Storage capacity	Built-in microSD/SDHC/SDXC slot, up to 128 GB
Standards	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP,SMTP, SNMP, IGMP, 802.1X, QoS, IPv6
Video format	H.265, H.264, MJPEG
Weatherproof rating	IP67
General features	rotate mode. Brightness, contrast, saturation, and sharpness are adjustable via web browser.120dB Wide Dynamic Range
Product weight (kg)	1,2
Product breadth (mm)	104,8
Product depth (mm)	258,6
Product height (mm)	104,8
Color	White
EAN	4015867202319
Model number	FCS-5092
Package contents	FCS-5092 Screw Kit Quick Installation Guide Resource CD (User Manual, Utility, QIG)
MicroSD/TF card slot	Built-in microSD/SDHC/SDXC slot, up to 128 GB
Resolutions	2592*1944@20fps
Camera Type	Bullet
Resistance	Weatherproof
Zoom Type	Fixed
IR Leds for night vision	Yes

